



DECLARATION of Conformity

Certificate No.: ZKS24006442

申請者
Holder of Certificate : Shenzhen Huapeng Era Technology Co., Ltd
Workshop 101-401, Building A, No.13, Jinlong Second Road, Tongle
Community, Baolong Street, Longgang District, Shenzhen China

製造者／輸入者
Manufacturer/ Importer : Shenzhen Huapeng Era Technology Co., Ltd
Workshop 101-401, Building A, No.13, Jinlong Second Road, Tongle
Community, Baolong Street, Longgang District, Shenzhen China

試験品
Description of Product : Lithium-ion Battery

識別表示
Model No. : 803035-800mAh

Trade Mark : N/A

適用した試験基準
Test Standards : 電気用品の技術上の基準を定める省令の解釈(R05.08.01) 別表第十二
Interpretation for METI Ordinance of Technical Requirements
(R05.08.01)
Appendix 12, J62133-2(2021)
(JIS C 62133-2:2020)

試験報告書番号
Test Report No. : DSP24110340-1

The evaluation is based on Article 8, Clause 1 of the electrical appliance and Material Safety Law (hereinafter, "the Law") but not based on Clause 2 of the said article and article 9. Under the Law, The designated products are classified to either "Specified Electrical Appliances and Materials" or "Non-Specified Electrical Appliances and Materials". This certificate is for products classified to "Non-specified Electrical Appliances and Materials." The "Reporting Supplier", who has been specified in Article 3 of the law, shall observe the requirements of the relevant articles of the law, i.e., Article 3, Article 8, Article 10 and other articles if any, and shall indicate the below-shown symbol suitably.



Certification Body

Frank Feng / General Manager



Date: 2024-12-30

Dongguan ZRLK Testing Technology Co., Ltd.

Building 2, No.1, Technology 10th Road, Songshan Lake Park, Dongguan, Guangdong, China

Tel.: +86-769-26621775

Website: www.zrlklab.com

【Authorized Valid Copy】

Type classification 型式の区分

要素 Factor	区分 Classification
単電池の形状 Shape of secondary cell	☐ 円筒形のもの Cylindrical ☒ 角形のもの Angular ☐ その他のもの Other
単電池の電解質の種類 Type of electrolyte in secondary cell	☒ 液体状のもの Liquid state ☐ その他のもの Other
単電池の上限充電電圧 Upper-limit charge voltage of secondary cell	☒ 4.25V以下のもの 4.25V or less ☐ 4.25Vを超えるもの More than 4.25V
組電池の質量 Weight of secondary battery	☒ 7 kg 以下のもの 7 kg or less ☐ 7 kg を超えるもの More than 7 kg
電池ブロックの個数 Number of battery blocks	☒ 1 個のもの Single ☐ 2 個以上のもの Multiple
過充電の保護機能 Overcharge protection	☒ 組電池で制御するもの Controlled by secondary battery ☐ 組電池搭載機器又は充電器で制御するもの Controlled by equipment incorporating a secondary battery or a charger
用途 Uses	☒ 携帯機器用のもの For mobile equipment ☐ 卓上機器用のもの For desktop equipment ☐ その他のもの Other
組電池の種類 Type of secondary battery	☒ はんだ付けその他の接合方法により、容易に取り外すことができない状態で機械器具に固定して用いられるものその他の特殊な構造のもの Those designed to fix to appliances by soldering or other joining methods so that it cannot be easily removed, or those having other special construction ☐ その他のもの Other